

## [GECS Knowledge Base](#)

**Topic:** Installing the GECS Agent for MPE/iX

**Created:** January 5, 2005

**Version:** GECS 3.5 and greater

**Author:** GECS Development

**Category:** Installation



**G L O B A L E C S**

## Installing the GECS Agent for MPE/iX

A. Go to a computer running Windows.

B. Enter

```
MD C:\GECSTOR
```

C. Download the MPE/iX Store File from the GECS web site as

```
C:\GECSTOR\GECSTOR
```

D. Enter

```
C:
```

```
CD \GECSTOR
```

E. Start an FTP session with the computer running MPE/iX by entering:

```
FTP computername
```

(where *computername* is the IP name or number of the computer running MPE/iX).

F. Login to the computer running MPE/iX as MANAGER.SYS

G. Enter

```
BINARY
```

```
PUT GECSTOR GECSTOR;REC=-1024,,B;DISC=16384000
```

```
QUIT
```

H. Go to the computer running MPE/iX

I. Login as MANAGER.SYS

J. Enter

```
NEWGROUP GECS.SYS;CAP=PH,IA,BA
```

```
FILE GECSTOR;DEV=DISC
```

```
RESTORE *GECSTOR;@.GECS.SYS;SHOW
```

K. Using a text editor, create the following file named JRUNAGNT.GECS.SYS:

```
!job jrunagnt, manager.sys
```

```
!run geCSagnt.gecs.sys;info="-n agentname -p 2000"
```

```
!eoj
```

where *agentname* is the name of this agent as it will be referenced in GECS

To start the agent run the script you created above, or enter:

```
GECSAGNT.GECS.SYS;info="-n agentname -v"
```