

GECS Knowledge Base

Topic: Installing the GECS Agent for OS/400

Created: January 5, 2005

Version: GECS 3.5 and greater

Author: GECS Development

Category: Installation



G L O B A L E C S

Installing the GECS Agent for OS/400

- A. Go to the computer running OS/400.
- B. Login as QSECOFR
- C. Enter

```
CRTLIB LIB(GECSLIB)
CRTSAVF FILE(GECSLIB/GECSSAVF)
```
- D. Go to a computer running Windows.
- E. Enter

```
MD C:\GECSTFILE
```
- F. Download the OS/400 Save File from the GECS web site as C:\GECSTFILE\GECSSAVF
*** On the GECS web site, the file will have a six digit number appended to the name.
Save it on your system **without** the six digit number
- G. Open a command shell (Start->Run->CMD.EXE)
- H. Enter

```
C:
CD \GECSTFILE
```
- I. Start an FTP session with the computer running OS/400 by entering:

```
FTP computername
```

(where *computername* is the IP name or number of the computer running OS/400).
- J. Login to the computer running OS/400 as QSECOFR
- K. Enter

```
BINARY
PUT GECSSAVF GECSLIB/GECSSAVF (REPLACE
Note that there is NO closing parenthesis on the above command.
QUIT
```
- L. Go back to the computer that is running OS/400.
- M. Enter

```
RSTLIB SAVLIB(GECSLIB) DEV(*SAVF) SAVF(GECSLIB/GECSSAVF)
```

To start the agent, enter:

```
SBMJOB CMD(call pgm(gecslib/gecsagnt) parm('-n agentname' '-v')) ALWMLTTHD(*YES)
```